



Efficiency Rating  
A++



Titanium Apatite  
deodorisation



Low as 21dBA



Turbo Mode

## FTXF-A/C RXF-A/B/C

The residential wall mount unit provides perfect comfort without compromising energy efficiency.

The flat front panel blends in easily with any interior décor and is easy to clean. Air is distributed efficiently and evenly, thanks to auto-swing louvres, which direct the discharge air downwards or upwards. The turbo mode means that the room can heat up or cool down rapidly.

### Seasonal efficiency values up to A++

The heat exchanger and fan generate one of the highest energy efficiencies across the range (20-60).

### Residential Controller App (optional)

The Residential Controller App controls your indoor unit from any location via connection to the cloud. Main functions like temperature set point, operation mode, fan speed, etc can also be controlled via Amazon Alexa or Google Assistant.


### Quiet operation down to 20 dB(A)

The different fan settings mean the residential wall mounted unit can be used in offices, hallways, living and bedrooms. With a sound pressure of 20 d(BA), the unit is whisper quiet.

### Reliable performance

The extensively tested swing compressor uses inverter technology and small capacity steps to adjust a unit's power and energy demands, delivering energy savings and vibration-free operation.

AVAILABLE COLOURS



**R32**  
technology

Efficiency data				FTXF + RXF	20A + 20A	25A + 25A	35A + 35A	50A + 50A	60A + 60A
Cooling capacity	Min./Nom./Max.		kW		1.3/2.00/2.6	1.3/2.50/3.0	1.3/3.30/3.8	1.7/5.00/6.0	1.7/6.00/7.0
Heating capacity	Min./Nom./Max.		kW		1.30/2.50/3.50	1.30/2.80/4.00	1.30/3.50/4.80	1.70/6.00/7.70	1.70/6.40/8.00
Power input	Cooling	Min./Nom./Max.	kW		0.31/0.51/0.72	0.31/0.76/1.05	0.29/1.00/1.30	0.32/1.50/1.83	0.33/1.85/2.98
	Heating	Min./Nom./Max.	kW		0.25/0.60/0.95	0.25/0.70/1.11	0.29/0.94/1.29	0.44/1.62/2.36	0.46/1.63/2.79
Space cooling	Energy efficiency class				A++				
	Capacity	Pdesign	kW		2.00	2.50	3.50	5.00	6.00
	SEER				6.15	6.22		6.21	6.15
	Annual energy consumption		kWh/a		114	141	197	282	342
Space heating (Average climate)	Energy efficiency class				A+				
	Capacity	Pdesign	kW		2.20	2.40	2.80	4.60	4.80
	SCOP/A				4.10			4.06	
	Annual energy consumption		kWh/a		751	827	965	1,584	1,655
Nominal efficiency	EER				3.94		3.30	3.33	3.25
	COP				4.19	4.01		3.71	3.93
Energy labeling Directive Cooling/Heating					A/A				
Indoor unit				FTXF	20A	25A	35A	50A	60A
Dimensions	Unit	HeightxWidthxDepth	mm		286x770x225			295x990x263	
Weight	Unit		kg		9.00			13.5	
Air filter	Type				Removable / washable				
Fan	Air flow rate	Cooling	Silent operation/Low/Medium/High m <sup>3</sup> /min		4.4/5.9/7.9/9.8	4.4/6.1/8.1/10.1	4.5/6.3/8.3/11.5	10.5/11.9/14.4/16.8	10.7/12.2/14.8/17.3
		Heating	Silent operation/Low/Medium/High m <sup>3</sup> /min		5.3/6.5/8.4/10.3	5.3/6.7/8.6/10.3	5.3/7.0/9.0/11.5	10.7/12.2/14.8/17.3	11.3/12.8/15.8/17.9
Sound power level	Cooling/Heating		dB(A)		55/55		58/58	59/61	60/62
Sound pressure level	Cooling	Silent operation/Low/High	dB(A)		20/25/39	20/26/40	20/27/43	31/34/43	33/36/45
	Heating	Silent operation/Low/High	dB(A)		21/28/39	21/28/40	21/29/40	30/33/42	32/35/44
Control systems	Infrared remote control				ARC470A1				
	Wired remote control				BRC944B2 / BRC073A1				
Power supply	Phase/Frequency/Voltage		Hz/V		1~/50/220-240				
Outdoor unit				RXF	20A	25A	35A	50A	60A
Dimensions	Unit	HeightxWidthxDepth	mm		550x658x275			735x825x300	
Weight	Unit		kg		28			47	
Sound power level	Cooling/Heating		dB(A)		60/61		62/62	61/61	63/63
Sound pressure level	Cooling	High	dB(A)		46		48	47	49
	Heating	High	dB(A)		47		48		49
Refrigerant	Type/ GWP				R-32/675.0				
	Charge		kg/TCO <sub>2</sub> Eq		0.70/0.48			1.40/0.95	1.45/0.98
Piping connections	Liquid	OD	mm		6.35			6.4	
	Gas	OD	mm		9.5			12.7	
	Piping length	OU - IU	Max.	m	15			30	
	Additional refrigerant charge		kg/m		0.02 (for piping length exceeding 10m)				
Level difference	IU - OU	Max.	m		12			20.0	
Power supply	Phase/Frequency/Voltage		Hz/V		1~/50/220-240				

Accessory Ref	Description
EKRS21	Wire harness for new S21 port for all marked (*) options - required for FTXF-C only
BRC073*	Optional wired remote controller BRC1E53A style - Connection cable required.
BRP069B45	Wifi adaptor for connection to online controller
BRCW901A03	3m connection cable for BRC073
BRCW901A08	8m connection cable for BRC073
K.CWB90-2	Condensing unit bracket - up to size 71, max weight 90kg of ODU
K.DT1	Condensate drip tray for use with Split ODU - tray width 800mm
K.CGS	Condensing Unit Guard size 20-35
K.CGM	Condensing Unit Guard size 42-71

### Notes

- > All fan coils are supplied with infrared remote controller ARC470A1
- > Whisper quiet in operation down to 20 dBA
- > The unit's compact dimensions makes it ideal for renovation projects, especially for above door installation
- > Space saving contemporary wall mounted design

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)